



The all-rounder
HKS TiltRotator

2 x 55° tilting and continuous rotating at the same time

One HKS TiltRotator for all attachments

You will achieve unimaginable operating positions

Thanks to the **HKS TiltRotator**, you are able to tilt your attachment $\pm 55^\circ$ in both directions and rotate continuously at the same time. Both functions enable you to achieve tree-dimensional positioning easily and accurately. This increases your efficiency and productivity.

With its compact and robust tilt unit, the **HKS TiltRotator** is the perfect enhancement to any conventional wider cylinder variants that are prone to faults. An optimised **HKS XtraTilt** with an extended torque and a reduced overall height is used for the **HKS TiltRotator**.

Details

- ▶ Standard tilt angle of 2 x 55° (2 x 70° upon request)
- ▶ Holding torque of up to 90,000 Nm
- ▶ Torque of up to 43,000 Nm
- ▶ 10 designs for carrier device weights of up to 45 t
- ▶ Up to 8 rotations per minute
- ▶ Modular system

Applications

- ▶ Garden and landscaping work
- ▶ Trench digging
- ▶ Road construction
- ▶ Demolition work
- ▶ Civil engineering
- ▶ Backfilling during construction work
- ▶ Foundation work
- ▶ Embankment work
- ▶ Metering work
- ▶ Work on inclined planes (hillsides)
- ▶ Hydraulic hammer and milling insert (limited warranty)

